

# Table Lubricant

# 7376

## Lubricant and Parting Agent for Woodworking Machines

### DESCRIPTION

**Callington Table Lubricant** is a woodworking parting agent formulated on high quality white oil, and is designed to meet the lubrication requirements of most woodworking machines. It is safe to use, colourless and odourless therefore providing a pleasant working environment.

### APPLICATION

**Callington Table lubricant** can be applied by hand, or by spray if the machine is equipped with a spray dosing system. With a suitable pump system the amount of lubricant can be optimised, depending on the nature of the wood (i.e. hard or soft).

The product is silicon free which ensures no problems are encountered with further processes such as gluing, staining or painting, although the wood surface coated with the lubricant must be cleaned of oil residue by subsequent machining, such as planing or sanding.

It also provides excellent water separation properties and oxidation resistance, providing corrosion resistance to metal surfaces, and preventing build up and blockages in pipes and spray nozzles.

### BENEFITS

- Colourless, odourless and safe to use. Excellent operator acceptance.
- Excellent lubrication and parting properties means easy operation.
- Water repelling, provides corrosion protection to metal machine parts.
- Excellent oxidation resistance means no sticky build up, no blocking of pipes and spray nozzles.
- Silicon free, so compatible with subsequent gluing or coating operations.
- Low viscosity product, easy to pump, excellent wetting properties and non blocking.

Metal Working Fluid Technologies For Industry

TYPICAL DATA (note: data is typical; and does not constitute a specification)

Concentrate	Test method	Typical result
Appearance	Visual	Clear colourless liquid
Density @ 20C	DIN 51757, ASTM D1298	0.84
Kinematic Viscosity @ 40°C ( cSt)	ASTM D445	12.0
Flash Point ( °C)	ASTM D92	180 minimum
Pour Point (°C)	ASTM D97	-21.0 maximum

**Storage:** Keep container closed, prevent exposure to frost, and prevent water ingress. Store in cool, dry conditions, and avoid direct sunlight. Indoor storage is preferable.

**WARRANTY** – All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, expressed or implied, for which seller assumes legal responsibility and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.

**CALLINGTON HAVEN PTY LTD**



Incorporated in New South Wales  
 ACN 000 632 404 ABN 28 000 632 404  
 30 South Street Rydalmere NSW 2116  
 PO Box 144 Rydalmere NSW BC 1701 Australia  
 T: (61-2) 9898 2788 F: 9475 0449  
 E: [enquiries@calhaven.com.au](mailto:enquiries@calhaven.com.au) W: [www.callingtonhaven.com](http://www.callingtonhaven.com)

